

	Product Infomation SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
		Client Name	DPA
Project Name	Demo	Client Addr.	
Item Number	001	Contact Name	Alireza
		Telephone	

Product No.: 117408065020

Series description:

Simple structure

Rated Paramter

Flow(m³/h)	50
Height(m)	20
Eff(%)	62
Power(kW)	4.4
Impeller Dia(mm)	178
Speed(rpm)	2900

technology

Pump rotator speed	2900
Nameplate standards	CE

Material

Impeller	F46
Rubber code	F1
Material Code	F46

Installation

Maximum Operation Pressure:	10bar
Maximum Altitude	1000m

Medium

Medium Temperature	-15+120
Medium Density	1.35*10³kg/m³
Maximum Environment Temperature:	40

Structure dimension

Inlet size	DN80/PN10
Outlet Bore	DN65/PN10

Motor

Number of Motor Phase	Three Phase
Protection Class	IP55
Insulation Class	F
Motor Power	7.5KW
Power Frequency	50HZ
Rated Voltage (V)	380V
Rated Current (A)	14.5A
Energy Efficiency Level	IE2

Seal

Mechanical Seal	SZ-35/MST4
-----------------	------------


	Product Infomation SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
		Client Name	DPA
Project Name	Demo	Client Addr.	
Item Number	001	Contact Name	Alireza
		Telephone	

Others:

Weight (kg) 123


	Performance Curve SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
		Client Name	DPA
Project Name	Demo	Client Addr.	
Item Number	001	Contact Name	Alireza
		Telephone	

Medium Name:Clear Water,Temperature:20,Density:1000kg/m³,Viscosity:1mm²/s



	Technical parameters SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
Project Name	Demo	Client Name	DPA
Item Number	001	Client Addr.	
		Contact Name	Alireza
		Telephone	

Rated parameters	
Pump model	SZ80-65-125
Product No.	117408065020
Rated speed(r/min)	2900
Design point parameters	
Flow(m³/h)	
Head(m)	
Static head(m)	0
Operating point parameters	
Flow(m³/h)	
Head(m)	
Efficiency(%)	
Power(kW)	
Speed	
Impeller Diameter(mm)	178.00
Medium	
Medium Name	Clear Water
Working temperature(°C)	20
Medium density(kg/m³)	1000
Viscosity(mm²/s)	1



	Product information SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
Project Name	Demo	Client Name	DPA
Item Number	001	Client Addr.	
		Contact Name	Alireza
		Telephone	

Description	Value
-------------	-------

General information

Product model	SZ80-65-125
Product No.	117408065020

Rated Paramter

Flow(m³/h)	50
Height(m)	20
Eff(%)	62
Power(kW)	4.4
Impeller Dia(mm)	178
Speed(rpm)	2900

technology

Pump rotator speed	2900
Nameplate standards	CE

Material

Impeller	F46
Rubber code	F1
Material Code	F46

Installation

Maximum Operation Pressure:	10bar
Maximum Altitude	1000m

Medium

Medium Temperature	-15+120
Medium Density	1.35*10 ³ kg/m ³
Maximum Environment Temperature:	40

Structure dimension

Inlet size	DN80/PN10
Outlet Bore	DN65/PN10

Motor



Number of Motor Phase	Three Phase
Protection Class	IP55
Insulation Class	F
Motor Power	7.5KW
Power Frequency	50HZ
Rated Voltage (V)	380V
Rated Current (A)	14.5A
Energy Efficiency Level	IE2

Seal

Mechanical Seal	SZ-35/MST4
-----------------	------------


Others

Weight (kg)	123
-------------	-----




	Dimensional Drawing SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
Project Name	Demo	Client Name	DPA
Item Number	001	Client Addr.	
		Contact Name	Alireza
		Telephone	

SZ80-65-125



	Structure Drawing SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
		Client Name	DPA
Project Name	Demo	Client Addr.	
Item Number	001	Contact Name	Alireza
		Telephone	



	Order data SZ80-65-125	Manufacturer	CNP
		Address	
		Telephone	400-826-7722
		Date	3/8/2022
Project Name	Demo	Client Name	DPA
Item Number	001	Client Addr.	
		Contact Name	Alireza
		Telephone	

Pump model:

SZ80-65-125

Product No.:

117408065020

Product price:

Product quantity:

1

Total: inquiry:

Inquiry notes: