

 CNP 南方泵业	Product Information SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Part NO.	1100050822		
Product Picture: (Note: Images may not be the same as the product)		Note	
		Stainless steel multi-stage submersible pump is equipped with a submersible motor which can replace traditional long axis Deep-well pump.The pump is also equipped with a check valve to protect itself from reflux and water hammer.	

Nameplate parameters

Flow	5 m ³ /h
Head	98 m
Efficiency	53 %
Speed	2850 rpm
Number of stages	26

Material

Impeller	304
Material Code	F

Installation

Operation Pressure	24bar
Maximum Immersion Depth	70m
Maximum Operation Pressure	38bar

Medium

Medium Temperature	15~40°C
Medium PH Value	6.5~8.5
Liquid Temperature Range	+25°C

Structure dimension

Rotation Direction	Anti-clockwise rotation viewing from outlet
Explosed view	SJ1,3,5 exploded view


Motor

Number of Motor Phase	Three Phase
Protection Class	IP68
Insulation Class	F
Motor Power(kW)	3KW
Power Frequency(Hz)	50HZ
Rated Voltage (V)	380

Others

Weight (kg)	29
-------------	----

	Performance Curve SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



 CNP 南方泵业	Pump Technical Parameters SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Rated parameters	
Pump model	SJ5-26
Part NO.	1100050822
Rated flow	5 m³/h
Rated head	98 m
Rated efficiency	53 (%)
Power (kW)	2.52 kW
Speed (rpm)	2850
Max impeller diameter (mm)	73
Medium	
Pumped medium	water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1

The image displays three performance graphs for the SJ5-26 pump, plotted against flow rate (Q) in m³/h. The top graph shows Head (H) in meters, the middle graph shows Power (P) in kW, and the bottom graph shows Efficiency (η) in percent. All three graphs share a common x-axis ranging from 0 to 6 m³/h.


Head (H) vs Flow (Q): The head decreases as flow increases, starting at approximately 150 m at 0 m³/h and dropping to about 50 m at 6 m³/h.

Power (P) vs Flow (Q): The power increases with flow, starting at approximately 0.8 kW at 0 m³/h, peaking at about 2.3 kW around 5 m³/h, and then slightly decreasing to 2.2 kW at 6 m³/h.


Efficiency (η) vs Flow (Q): The efficiency increases with flow, starting at 0% at 0 m³/h, peaking at approximately 60% around 4 m³/h, and then decreasing to about 40% at 6 m³/h.

Q (m³/h)	H (m)	P (kW)	η (%)
0	150	0.8	0
1	145	1.1	25
2	138	1.4	45
3	128	1.7	55
4	115	2.0	60
5	95	2.3	55
6	50	2.2	40

 CNP 南方泵业	Dimension Drawing SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Explosed view SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



 CNP 南方泵业	Physical picture SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Order Data SJ5-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Pump model SJ5-26
Part NO. 1100050822
Product price
Quantity 1
Total price

Inquiry notes