

 CNP 南方泵业	Product Information SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Part NO.	1100050995		
Product Picture: (Note: Images may not be the same as the product)		Note	
		Stainless steel multi-stage submersible pump is equipped with a submersible motor which can replace traditional long axis Deep-well pump.The pump is also equipped with a check valve to protect itself from reflux and water hammer.	

Nameplate parameters

Flow	8 m ³ /h
Head	67 m
Efficiency	56 %
Speed	2850 rpm
Number of stages	17

Material

Impeller	304
Material Code	F

Installation

Operation Pressure	27bar
Maximum Immersion Depth	70m
Maximum Operation Pressure	38bar

Medium

Medium Temperature	15~40°C
Medium PH Value	6.5~8.5
Liquid Temperature Range	+25°C

Structure dimension

Rotation Direction	Anti-clockwise rotation viewing from outlet
Explosed view	SJ8exploded view


Motor

Number of Motor Phase	Three Phase
Protection Class	IP68
Insulation Class	F
Motor Power(kW)	3KW
Power Frequency(Hz)	50HZ
Rated Voltage (V)	380

Others

Weight (kg)	32
-------------	----

 CNP 南方泵业	Performance Curve SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	




 CNP 南方泵业	Pump Technical Parameters SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Rated parameters	
Pump model	SJ8-17
Part NO.	1100050995
Rated flow	8 m³/h
Rated head	67 m
Rated efficiency	56 (%)
Power (kW)	2.61 kW
Speed (rpm)	2850
Max impeller diameter (mm)	75
Medium	
Pumped medium	water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1


The figure contains three vertically stacked line graphs sharing a common x-axis representing flow rate Q in m³/h, ranging from 0 to 10. The top graph shows Head H in meters (m), starting at approximately 100m at Q=0 and decreasing to about 40m at Q=10. The middle graph shows Power P in kilowatts (kW), starting at about 1.0 kW at Q=0, peaking at approximately 2.4 kW around Q=8, and then slightly decreasing. The bottom graph shows Efficiency η in percent (%), starting at 0% at Q=0, peaking at about 60% around Q=8, and then slightly decreasing.

Q (m³/h)	H (m)	P (kW)	η (%)
0	100	1.0	0
2	95	1.4	30
4	88	1.9	48
6	78	2.3	58
8	67	2.4	60
10	40	2.2	56

 CNP 南方泵业	Dimension Drawing SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Explosed view SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



E-SJ 8-151103

 CNP 南方泵业	Physical picture SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Order Data SJ8-17	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Pump model SJ8-17
Part NO. 1100050995
Product price
Quantity 1
Total price

Inquiry notes