

 CNP 南方泵业	Product Information SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Part NO.	1100051345		
Product Picture: (Note: Images may not be the same as the product)		Note	
		Stainless steel multi-stage submersible pump is equipped with a submersible motor which can replace traditional long axis Deep-well pump.The pump is also equipped with a check valve to protect itself from reflux and water hammer.	

Nameplate parameters

Flow	12 m ³ /h
Head	111 m
Efficiency	59 %
Speed	2850 rpm
Number of stages	22

Material

Impeller	304
Material Code	F

Installation

Operation Pressure	16bar
Maximum Immersion Depth	70m
Maximum Operation Pressure	38bar

Medium

Medium Temperature	15~40°C
Medium PH Value	6.5~8.5
Liquid Temperature Range	+25°C

Structure dimension

Rotation Direction	Anti-clockwise rotation viewing from outlet
Explosed view	SJ12 exploded view

Motor


Number of Motor Phase	Three Phase
Protection Class	IP68
Insulation Class	F
Motor Power(kW)	7.5KW
Power Frequency(Hz)	50HZ
Rated Voltage (V)	380

Others

Weight (kg)	49
-------------	----

 CNP 南方泵业	Performance Curve SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

The hydraulic performance curve have been tested with water at 20°C, density 1000kg/m³,and at 1bar atmospherical pressure. ISO99062012 Grade 3B




 CNP 南方泵业	Pump Technical Parameters SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Rated parameters	
Pump model	SJ12-22
Part NO.	1100051345
Rated flow	12 m³/h
Rated head	111 m
Rated efficiency	59 (%)
Power (kW)	6.15 kW
Speed (rpm)	2850
Max impeller diameter (mm)	80
Medium	
Pumped medium	water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1


The image displays three performance graphs for the SJ12-22 pump, plotted against flow rate (Q) in m³/h. The x-axis for all graphs ranges from 0 to 16 m³/h, with major grid lines every 4 units. The top graph shows Head (H) in meters, starting at approximately 150m at 0 m³/h and decreasing to about 60m at 16 m³/h. The middle graph shows Power (P) in kW, starting at approximately 2.5kW at 0 m³/h, rising to a peak of about 6.5kW at 14 m³/h, and then slightly decreasing. The bottom graph shows Efficiency (η) in percent, starting at 0% at 0 m³/h, rising to a peak of about 60% at 12 m³/h, and then decreasing to about 48% at 16 m³/h.

Q (m³/h)	H (m)	P (kW)	η (%)
0	150	2.5	0
4	145	3.5	40
8	130	5.0	55
12	110	6.0	60
16	60	6.3	48

 CNP 南方泵业	Dimension Drawing SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Explosed view SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



E-SJ 12-151103

 CNP 南方泵业	Physical picture SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Order Data SJ12-22	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Pump model SJ12-22
Part NO. 1100051345
Product price
Quantity 1
Total price

Inquiry notes