

 CNP 南方泵业	Product Information SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Part NO.	1100052410		
Product Picture: (Note: Images may not be the same as the product)		Note	
		Stainless steel multi-stage submersible pump is equipped with a submersible motor which can replace traditional long axis Deep-well pump.The pump is also equipped with a check valve to protect itself from reflux and water hammer.	

Nameplate parameters

Flow	75 m ³ /h
Head	79 m
Efficiency	73 %
Speed	2900 rpm
Number of stages	6

Material

Impeller	304
Material Code	F

Installation

Operation Pressure	38bar
Maximum Immersion Depth	70m
Maximum Operation Pressure	38bar

Medium

Medium Temperature	15~40°C
Medium PH Value	6.5~8.5
Liquid Temperature Range	+25°C

Structure dimension

Rotation Direction	Anti-clockwise rotation viewing from outlet
Explosed view	SJ75,95exploded view


Motor

Number of Motor Phase	Three Phase
Protection Class	IP68
Insulation Class	F
Motor Power(kW)	22KW
Power Frequency(Hz)	50HZ
Rated Voltage (V)	380

Others

Weight (kg)	141
-------------	-----

 CNP 南方泵业	Performance Curve SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	




 CNP 南方泵业	Pump Technical Parameters SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Rated parameters	
Pump model	SJ75-6
Part NO.	1100052410
Rated flow	75 m³/h
Rated head	79 m
Rated efficiency	73 (%)
Power (kW)	22.1 kW
Speed (rpm)	2900
Max impeller diameter (mm)	130
Medium	
Pumped medium	water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1


The graphs show the performance characteristics of the SJ75-6 pump. The top graph shows Head (H) in meters decreasing from approximately 115m at 0 m³/h to 45m at 90 m³/h. The middle graph shows Power (P) in kW increasing from about 10 kW at 0 m³/h to a peak of 18 kW at 70 m³/h, then slightly decreasing. The bottom graph shows Efficiency (η) in percent increasing from 0% at 0 m³/h to a peak of 80% at 70 m³/h, then decreasing to about 65% at 90 m³/h.

Flow Rate (Q) [m³/h]	Head (H) [m]	Power (P) [kW]	Efficiency (η) [%]
0	115	10	0
20	112	13	40
40	105	16	65
60	95	17.5	78
75	85	18	80
90	45	17.5	65

 CNP 南方泵业	Dimension Drawing SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Explosed view SJ75-6	Manufacturer	Nanfeng Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



E-SJ 75, 95-090903

 CNP 南方泵业	Physical picture SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Order Data SJ75-6	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Pump model SJ75-6
Part NO. 1100052410
Product price
Quantity 1
Total price

Inquiry notes