

 CNP 南方泵业	Product Information SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Part NO.	1100050339
Product Picture: (Note: Images may not be the same as the product)	Note
	Stainless steel multi-stage submersible pump is equipped with a submersible motor which can replace traditional long axis Deep-well pump.The pump is also equipped with a check valve to protect itself from reflux and water hammer.

Nameplate parameters

Flow	1 m ³ /h
Head	134 m
Efficiency	38 %
Speed	2850 rpm
Number of stages	26

Material

Impeller	304
Material Code	F

Installation

Operation Pressure	28bar
Maximum Immersion Depth	70m
Maximum Operation Pressure	38bar

Medium

Medium Temperature	15~40°C
Medium PH Value	6.5~8.5
Liquid Temperature Range	+25°C

Structure dimension

Rotation Direction	Anti-clockwise rotation viewing from outlet
Explosed view	SJ1,3,5 exploded view


Motor

Number of Motor Phase	Three Phase
Protection Class	IP68
Insulation Class	F
Motor Power(kW)	1.5KW
Power Frequency(Hz)	50HZ
Rated Voltage (V)	380

Others

Weight (kg)	22
-------------	----

	Performance Curve SJ1-26	Manufacturer	Nanfeng Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	




 CNP 南方泵业	Pump Technical Parameters SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Rated parameters	
Pump model	SJ1-26
Part NO.	1100050339
Rated flow	1 m³/h
Rated head	134 m
Rated efficiency	38 (%)
Power (kW)	0.96 kW
Speed (rpm)	2850
Max impeller diameter (mm)	73
Medium	
Pumped medium	water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1


The figure displays three performance graphs for the SJ1-26 pump, plotted against flow rate (Q) in m³/h. The x-axis for all graphs ranges from 0 to 1.8 m³/h with major grid lines every 0.4 units and minor grid lines every 0.2 units.

- Head (H) in meters:** The top graph shows a decreasing curve starting at approximately 148 m at 0 m³/h and ending at approximately 85 m at 1.8 m³/h.
- Power (P) in kW:** The middle graph shows an increasing curve starting at approximately 0.42 kW at 0 m³/h and reaching a plateau of about 0.94 kW between 1.4 and 1.8 m³/h.
- Efficiency (η) in %:** The bottom graph shows an increasing curve starting at 0% at 0 m³/h, peaking at approximately 45% around 1.2 m³/h, and then slightly decreasing to about 44% at 1.8 m³/h.

 CNP 南方泵业	Dimension Drawing SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Explosed view SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
Item NO		Client Addr.	
		Contacts	Wepko
		Contact	



 CNP 南方泵业	Physical picture SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
		Client Name	WEPKO
Project Name		Client Addr.	
Item NO		Contacts	Wepko
		Contact	



 CNP 南方泵业	Order Data SJ1-26	Manufacturer	Nanfang Pump Industry Co.,Ltd (CNP)
		Address	Hangzhou, Zhejiang, China
		Contact	86-571-88637351
		Date	2025/06/30
Project Name		Client Name	WEPKO
		Client Addr.	
Item NO		Contacts	Wepko
		Contact	

Pump model SJ1-26
Part NO. 1100050339
Product price
Quantity 1
Total price

Inquiry notes