

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

Item n° : Customer pos. no.:

60167341

Model :

DCM-G 150-1600/A/BAQE/11 IE3

Pump data

MEI $\geq 0,60$

Pressure rating : PN 16
Min. fluid temperature : -10 °C
Max. fluid temperature : 140 °C
Max. Ambient temperature : 40 °C

Requested data

Flow :
Head :
Fluid (%) :
Fluid Temperature : 20 °C
Density : 998,3 kg/m³
Kinematic viscosity : 1,005 mm²/s
Vapor pressure : 0,34 psi

Hydraulic data (duty point)

Flow :
Head :
NPSH :
Shaft power P2 :
Efficiency :



Materials

Pump body Cast iron 250 UNI ISO 185
Support Cast iron 250 UNI ISO 185
Impeller Cast iron 250 UNI ISO 185
Mechanical seal SEE "SHAFT SEAL" SECTION
O-Ring EPDM Rubber
Shaft with rotor AISI 304 X5 Cr Ni 1810 UNI 6900/71

Motor data

Motor brand :
Nominal power P2 : 1 X 11 kW
Rated speed : 1.472 1/min
Rated voltage : 3~ 400 V 50 Hz
Nominal current : 1 X 20,5 A
Degree of protection : IP 55

Curve tolerance according to ISO 9906
Number of working motors : 1



Weight : 534 kg

Dimensions in mm

A	500	D2	285	L2	504
B	805	D3	240	M	M16
B1	550	D4	8 x Ø22	N	300
B2	580	H	1.061		
Bmax	1.130	H1	215		
C	925	H2	100		
D	150	L	800		
D1	210	L1	296		

Pump connection

Suction side : DN 150 / PN 16
Discharge side : DN 150 / PN 16

Receiver


From

Company
Reference
Address
Phone
Fax
E-mail

DCM-G 150-1600/A/BAQE/11 IE3

Number of working motors : 1

Curve tolerance according to ISO 9906



Suction side :

DN 150

PN 16

Discharge side :

DN 150

PN 16

Flow :

Head :

Rated speed :

1.472 1/min

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2025-08-04



DIMENSIONAL DRAWING

2025-08-04

Page 3 / 3





DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

DCM-G 150-1600/A/BAQE/11 IE3



Dimensions in mm

Pump connection

1	A	500	H	1.061			
2	B	805	H1	215			Suction
3	B1	550	H2	100			DN 150
4	B2	580	L	800			PN 16
5	Bmax	1.130	L1	296			
6	C	925	L2	504			
7	D	150	M	M16			Discharge
8	D1	210	N	300			DN 150
9	D2	285					PN 16
10	D3	240					
11	D4	8 x Ø22					

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2025-08-04