

Receiver

Company
Reference
Address
Phone
Fax
E-mail

From

Item n° : Customer pos. no.:

1D4111BAV

Model :

NKP-G 65-125/137/A/BAQE/7,5/2 IE3

Pump data

Impeller size (mm) : 137

MEI $\geq$ 0,40

Pressure rating : PN 16

Min. fluid temperature : -10 °C

Max. fluid temperature : 140 °C

Max. Ambient temperature : 50 °C

Requested data

Flow :

Head :

Fluid (%) :

Fluid Temperature : 20 °C

Density : 998,3 kg/m³

Kinematic viscosity : 1,005 mm²/s

Vapor pressure : 0,34 psi

Real duty point

Flow :

Head :

NPSH :

Shaft power P2 :

Efficiency :

Materials

Pump body Cast iron 250 UNI ISO 185

Support Cast iron 250 UNI ISO 185

Impeller Cast iron 250 UNI ISO 185

Mechanical seal SEE "SHAFT SEAL" SECTION

O-Ring Ethylene propylene (EPDM)

Pump shaft AISI 304 X5 Cr Ni 1810 UNI 6900/71

Seal spacer AISI 304 X5 Cr Ni 1810 UNI 6900/71

Shaft seal

Type Rubber

Stationary part Silicon carbide

Rotating part Carbon

Elastomer EPDM

Motor data

Nominal power P2 : 7,5 kW

Rated speed : 2.900 1/min

Rated voltage : 3~ 400 V



Nominal current : 13,4 A

Degree of protection : IP 55

2025-07-20

Page 1 / 3

Curve tolerance according to ISO 9906



Weight : 94 kg

Dimensions in mm

A	100	L	313
B	65	M1	125
DNA	80	M2	95
DNM	65	N1	280
F	437	N2	212
G	300	S1	M10
H1	160	X	100
H2	180		

Pump connection


Suction side : DN 80 / PN 16

Discharge side : DN 65 / PN 16

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

NKP-G 65-125/137/A/BAQE/7,5/2 IE3
Curve tolerance according to ISO 9906


Suction side :
DN 80
PN 16

Discharge side :
DN 65
PN 16

Flow :

Head :

Rated speed :
2.900 1/min

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2025-07-20



DIMENSIONAL DRAWING

2025-07-20


Page 3 / 3

DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

From

Company
Reference
Address
Phone
Fax
E-mail

NKP-G 65-125/137/A/BAQE/7,5/2 IE3

Dimensions in mm

Pump connection

1	A	100	N1	280						
2	B	65	N2	212						
3	DNA	80	S1	M10						Suction
4	DNM	65	X	100						DN 80
5	F	437								PN 16
6	G	300								
7	H1	160								Discharge
8	H2	180								DN 65
9	L	313								PN 16
10	M1	125								
11	M2	95								

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

2025-07-20