

Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

Item n° :

60168480

Model :

NKV 65/6 T IE3

Pump data

MEI $\geq$ 0,70

Max pressure 362/58 psi

Min. fluid temperature : 5 °F

Max. fluid temperature : 248 °F

Max. Ambient temperature : 104 °F

Requested data

Flow : 0/00 US g.p.m.

Head : 0/00 m

Fluid (%) : Water, pure

Fluid Temperature : 68 °F

Density : 62/322 lb/ft³

Kinematic viscosity : 1/0818E-5 ft²/s

Vapor pressure : 2/34 kPa

Hydraulic data (duty point)

Flow :

Head :

NPSH :

Shaft power P2 :

Efficiency :

Materials

Pump body Cast iron with cataphoresis

Support Cast iron with cataphoresis

Impeller Stainless Steel (AISI 304)



Pump shaft AISI 431

Mechanical seal Silicon carbide/Graphite/EPDM

Diffuser body and diffuser Stainless Steel (AISI 304)

Discharge plug Stainless Steel (AISI 304)

Curve tolerance according to ISO 9906


Weight : 517 kg

Motor data

Nominal power P2 : 37 kW
Rated speed : 2960 rpm
Rated voltage : 3~ 400 V 50 Hz
Nominal current : 63 A
Degree of protection : IP 55

Pump connection

Suction side : DN 100 / PN 25
Discharge side : DN 100 / PN 25

Dimensions in mm

B1	240	H2	1222/6
B2	316	H2	1107
C	300	X	230
C	292	Y	180
D	365	Z	100
DNA	DN 100		
DNM	DN 100		
G1	190		
G2	265		
H	1892/6		
H	1687		
H1	140		